

Specifications	
Model No.	US-M6501P
Panel Size	65" TFT-LED
Display area(mm)/mode	1429.67(W) × 803.77(H) 16:9
Max Resolution Support	1920 × 1080
Pixel Pitch	0.744(H) × 0.744(V)
Color	16.7M
Brightness (nits)	600cd/m <sup>2</sup>
Contrast	3000:1
Visual Angle (H/V)	178° /178°
Response Time	5ms
Horizontal frequency	30-75KHZ
Vertical frequency	56-75KHZ
Life(hrs)	>60,000(hrs)
Input and output	
Composite video input	3 (BNC × 3)
YPbPr input	1 (BNC × 3)
S-video	2 (BNCx2)
VGA	1
DVI	1
HDMI	1
Composite video output	2 (BNCx2)
Video	
Color system	PAL/NTSC/SECAM
Compatible HDMI input/DVI	480P,576P,720P,1080I,1080P
3D Comb filter	Yes
Video reduction noise	Yes
OSD display( screen menu display)	
Menu language	Chinese/English
Power	
Power Supply	AC100V ~ 240V,50/60Hz
Maximum Power Consumption	≅ 360W
Standby Power Consumption	<=3W
Temperature	
Working temperature	0℃ ~ 50℃
Storage temperature	- 20℃ ~60℃
Working Humidity	10% ~ 90%
Storage humidity	10% ~ 90%
Appearance	
Panel color/appearance	White/black/customized

Panel color/appearance	White,black,customized
Case Material	Metal
Net weight	68kg
Installation	Wall-mounted